



## LC10SP

### Applications

- Touring performance
- Club, multi-function hall
- Church

### Feature

- Built-in amplifier, self-powered subwoofer with LC10
- Compact 15inch subwoofer speaker
- Extremely compact ,small enclosure, light weight




### Technical specification


- FREQUENCY RESPONSE: 40 Hz – 150 Hz ( ± 3 dB )
- NOMINAL COVERAGE: <sup>(-dB)</sup> Omnidirectional
- MAXIMUM SPL: 125 dB SPL peak
- DRIVERS: 1 × 15" woofer (75mm voice coil)
- POWER REQUIREMENT: 200–240V ~50–60Hz
- AMPLIFIER MODULE: Dual channel 1200W
- POWER REQUIREMENT: 0.82%
- SNR: 104dB
- OUTPUT ELECTRIC CIRCUIT: Class D circuit
- COOLING SYSTEM: Airflow from back to front, Forced cooling

### Physical data


- FREQUENCY RESPONSE: 371 × 641 × 600mm
- WEIGHT: 35 kg / 77 lbs
- CONNECTORS: XLR;POWER CON; NEUTRIK NL4; USB
- SPEAKER CABLES: 1+1 – ( NL4 NEUTRIK 1 ) ; 1+1 – ( NL4 NEUTRIK 2 )
- MATERIALS: 15mm 18mm Baltic birch plywood
- FINISH: Black Polyurea paintings
- GRILLE: Black epoxy mesh grille with acoustically reticulated cloth
- RIGGING: 0, -5° degree adjustable



Front



Side



Top

